

YDRQ2.E168970 - Tubing, Mechanical Protection and Fittings - Component

Tubing, Mechanical Protection and Fittings - Component

REIKU GMBH

Robert-Bosch-Strasse 3
Wiehl-Bomig, 51674 Germany

E168970

Cat. No.	Size Range, mm (Nominal)	Color	Max Operating Temp, °C	Outdoor Use
Thermoplastic tubings				
PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G				
	-	BK,GY	105	No
PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G				
	-	-	105	No
PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G				
	7 - 95	BK,GY	105	Yes
PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G				
	12-95	BK,GY	105	Yes
PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G				
	17-95	BK,GY	105	No
PURM(c)-70G	-	-	105	No
PURR(c)-52G, PURR(c)-70G				

	-	-	105	No
PURV(c)-52G, PURV(c)-70G				
	-	-	105	No

Cat. No.	Size Range, (Nominal) mm	Mounting Means	Orientation	Thread Configuration	Thread Type	Compatible with Tubing Series	Wet Locations	
Thermoplastic fittings								
PA(d)(g)(b)-07(e), PA(d)(g)(b)-10(e), PA(d)(g)(b)-12(e), PA(d)(g)(b)-17(e), PA(d)(g)(b)-23(e), PA(d)(g)(b)-29(e), PA(d)(g)(b)-36(e), PA(d)(g)(b)-48(e), PA(d)(g)(b)-52(e), PA(d)(g)(b)-70(e), PA(d)(g)(b)-95(e)								
	7 - 95	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, Other, PG	REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G
							REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No
							REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes
							REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes
							REIKU GMBH (E168970) Grade: PURV(c)-52G, PURV(c)-70G	No

							REIKU GMBH (E168970) Grade: PURR(c)-52G, PURR(c)-70G	No	
							REIKU GMBH (E168970) Grade: PURM(c)-70G	No	
							REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes	
PM(d)(a)(b)-07(e), PM(d)(a)(b)-10(e), PM(d)(a)(b)-12(e), PM(d)(a)(b)-17(e), PM(d)(a)(b)-23(e), PM(d)(a)(b)-29(e), PM(d)(a)(b)-36(e), PM(d)(a)(b)-48(e) X									
	7 - 48	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, Other, PG	REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes
							REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes	
							REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes	
							REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G	Yes	
							REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No	
VM(d)(f)(b)-10(e), VM(d)(f)(b)-12(e), VM(d)(f)(b)-17(e), VM(d)(f)(b)-23(e), VM(d)(f)(b)-29(e), VM(d)(f)(b)-36(e), VM(d)(f)(b)-48(e) X									

	10 - 48	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, PG	REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No
								REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes
VP(d)(f)(b)-10(e), VP(d)(f)(b)-12(e), VP(d)(f)(b)-17(e), VP(d)(f)(b)-23(e), VP(d)(f)(b)-29(e), VP(d)(f)(b)-36(e), VP(d)(f)(b)-48(e) X									
	10 - 48	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, Other, PG	REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No

	REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes
	REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes
	REIKU GMBH (E168970) Grade: PURV(c)-52G, PURV(c)-70G	No
	REIKU GMBH (E168970) Grade: PURR(c)-52G, PURR(c)-70G	No
	REIKU GMBH (E168970) Grade: PURM(c)-70G	No

(a) - Represents O for no inner seal, R for inner seal, or V for both outer flat washer and inner seal

(b) - Represents B for Black or G for Gray

(c) - Represents B for black

(d) - Represents G, B, W, S, A, I or F for the fitting design

(e) - Represents various codes, or be blank, for the thread details

(f) - Represents R for inner seal or V for both outer flat washer and inner seal

(g) - Represents O for no inner seal, R for inner seal or V for both outer flat washer and inner seal or D for both outer flat washer and inner seal on larger sizes

Marking: Company name, catalog designation, temperature rating on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2023-01-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission