

Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).

Tubing, Mechanical Protection and Fittings - Component

COMPANY

REIKU GMBH

Rudolf-Diesel-Str. 7

Wiehl-Bomig, D-51674 Germany

E168970

Cat. No.	Size Range, mm (Nominal)	Color	Max Operating Temp, °C	Outdoor Use
Thermoplastic tubings				
PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G				
	7 - 95	BK,GY	105	No
PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G				
	17 - 52 mm	BK	105	No
PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G				
	7 - 95	BK,GY	105	Yes
PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G				
	12-95	BK,GY	105	Yes
PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G				
	17-95	BK,GY	105	No
PURM(c)-70G	70	BK	105	No
PURR(c)-52G, PURR(c)-70G				
	52 - 70 mm	BK	105	No
PURV(c)-52G, PURV(c)-70G				
	52 - 70 mm	BK	105	No

Size Range, Cat. mm		Color	Type	Mounting Means	Orient- ation	Thread Configuration	Thread Type	Compatible with	Wet Locations
No. (Nominal)								Tubing Series	
Thermoplastic fittings									
PA(d)(g)(b)-07(e), PA(d)(g)(b)-10(e), PA(d)(g)(b)-12(e), PA(d)(g)(b)-17(e), PA(d)(g)(b)-23(e), PA(d)(g)(b)-29(e), PA(d)(g)(b)-36(e), PA(d)(g)(b)-48(e), PA(d)(g)(b)-52(e), PA(d)(g)(b)-70(e), PA(d)(g)(b)-95(e)									
	7 - 95	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, Other, PG	REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No
								REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes

								REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PURV(c)-52G, PURV(c)-70G	No
								REIKU GMBH (E168970) Grade: PURR(c)-52G, PURR(c)-70G	No
								REIKU GMBH (E168970) Grade: PURM(c)-70G	No
								REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes
PM(d)(a)(b)-07(e), PM(d)(a)(b)-10(e), PM(d)(a)(b)-12(e), PM(d)(a)(b)-17(e), PM(d)(a)(b)-23(e), PM(d)(a)(b)-29(e), PM(d)(a)(b)-36(e), PM(d)(a)(b)-48(e) X									
	7 - 48	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, Other, PG	REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes

	REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes
	REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes
	REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G	Yes

								REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No
VM(d)(f)(b)-10(e), VM(d)(f)(b)-12(e), VM(d)(f)(b)-17(e), VM(d)(f)(b)-23(e), VM(d)(f)(b)-29(e), VM(d)(f)(b)-36(e), VM(d)(f)(b)-48(e) X									
	10 - 48	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, PG	REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No
								REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes

								REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes
								REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes
VP(d)(f)(b)-10(e), VP(d)(f)(b)-12(e), VP(d)(f)(b)-17(e), VP(d)(f)(b)-23(e), VP(d)(f)(b)-29(e), VP(d)(f)(b)-36(e), VP(d)(f)(b)-48(e) X									
	10 - 48	BK,GY	Connector	Threaded	45 degree, 90 degree, Straight	Female, Male	Gas, Metric, NPT, Other, PG	REIKU GMBH (E168970) Grade: PARE(b)-07G, PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-42M, PARE(b)-48F, PARE(b)-52G, PARE(b)-70G, PARE(b)-95G	Yes

	REIKU GMBH (E168970) Grade: PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G	Yes
	REIKU GMBH (E168970) Grade: PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G	No
	REIKU GMBH (E168970) Grade: PARN(b)-07G, PARN(b)-10F, PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-42M, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G	Yes
	REIKU GMBH (E168970) Grade: PARR(b)-12F, PARR(b)-17F, PARR(b)-23F, PARR(b)-23G, PARR(b)-29F, PARR(b)-29G, PARR(b)-36F, PARR(b)-36G, PARR(b)-42M, PARR(b)-48F, PARR(b)-48G, PARR(b)-52G, PARR(b)-70G, PARR(b)-95G	Yes

	REIKU GMBH (E168970) Grade: PURV(c)-52G, PURV(c)-70G	No
	REIKU GMBH (E168970) Grade: PURR(c)-52G, PURR(c)-70G	No
	REIKU GMBH (E168970) Grade: PURM(c)-70G	No

(a) - Represents O for no inner seal, R for inner seal, or V for both outer flat washer and inner seal

(b) - Represents B for Black or G for Gray

(c) - Represents B for black

(d) - Represents G, B, W, S, A, I or F for the fitting design

(e) - Represents various codes, or be blank, for the thread details

(f) - Represents R for inner seal or V for both outer flat washer and inner seal

(g) - Represents O for no inner seal, R for inner seal or V for both outer flat washer and inner seal or D for both outer flat washer and inner seal on larger sizes

Marking: Company name, catalog designation, temperature rating on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2024-06-13

Der Umstand, dass der Name oder das Produkt eines Unternehmens in dieser Datenbank aufgeführt ist, garantiert nicht, dass die Herstellung der jeweiligen Produkte dem Follow-Up-Service von UL unterliegt. Nur Produkte mit UL-Zeichen gelten als zertifiziert und sind vom Follow-Up-Service von UL abgedeckt. Prüfen Sie daher stets, ob ein Produkt das UL-Zeichen trägt.

UL gestattet die Weiterverwendung der im Online-Zertifizierungsverzeichnis enthaltenen Materialien unter den folgenden Bedingungen: 1. Alle Anleitungen, Baugruppen, Konstruktionen, Designs, Systeme und/oder Zertifizierungen (Dateien) müssen vollständig und auf nicht irreführende Weise ohne Manipulation der Daten (oder Zeichnungen) dargestellt werden. 2. Bei Weiterverwendung von Materialien muss der Vermerk „Aus dem Online-Zertifizierungsverzeichnis mit Genehmigung von UL nachgedruckt“ stets mit angegeben werden. Darüber hinaus muss das nachgedruckte Material einen Urheberrechtsvermerk in folgendem Format enthalten: "©2025 UL LLC."